

## Water Treatment Plant 5 MGD Capacity Expansion New Raw Water Pump Station Livingston, TX



## PROJECT OVERVIEW AND CHALLENGES

Bradshaw was contracted to install twin 36 inch steel casings from a 30 foot deep pump station shaft at the shoreline of Lake Livingston Reservoir to an intake cofferdam in the lake. Each microtunneled casing was 390 foot long and used to install 24 inch ductile iron carrier pipes. The soil conditions consisted of clay and sandy silt 20 feet below the water table. Due to the non-cohesive soil conditions and shallow cover at the retrieval shaft in the lake, the MTBM recovery was performed under water by divers. Additional challenges included unusually heavy rainfall during microtunneling leading to significant flooding of the Livingston area.





## **PROJECT INFORMATION - 545**

OWNER: Trinity River Authority 817-467-4343

ENGINEER: Klotz Associates, Inc. Alexander Kuzovkov 281-589-7257

**CONTRACTOR:** Layne Heavy Civil, Inc.

**COMPLETION DATE:** 7/24/2015

**GEOLOGY:** Clay, Sand

EXCAVATION METHOD: Herrenknecht AVN-600 MTBM

MINING DIMENSIONS: 780' x 36" Ø

FINAL LINING: 24" Ductile Iron Pipe

## FOR MORE INFORMATION:

Mike Wanhatalo, Project Manager 410-970-8300 mwanhatalo@bradshawcc.com Refer to Project 545